IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

1.	Name/Description of battery
	58493 AKKUPACK GAP 12-20

### 1a. Name/Description of the cells inside the battery

### Qixin Power ICR 18650-2000mAh

The test summary of the cells inside the battery must either be presented or under checkpoint 9 and 9a it must be confirmed that the UN 38.3 test summary for the cells is available.

2. Manufacturer of battery				
Name	Güde GmbH & Co.KG			
Address	Birkichstr. 6; 74549 Wolpertshausen			
Phone	07904 / 700 112 info@guede.com			
Email				
Website www.guede.com				

2a. Manufacturer of the equipment (if the battery is contained in equipment)					
Name					
Address					
Phone					
Email					
Website					

3. Test laboratory of battery						
Name	JL-CCIC Company Limited Guangzhou Branch					
Address	No.8, Nanyun 2nd Road, Science City, Guangzhou Hi-Tech Development Zone, 😭					
Phone	+86-20-3213 1000					
Email	customerservice.cn@cn.ul.com					
Website	www.ul.com					

4. ID-number and date					
Unique test report identification number	4788962761-1	Date of test report	2018-8-18		



IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

58493 AKKUPACK GAP 12-20

#### **DESCRIPTION OF BATTERY**

5. Mark the type of battery with an "●"						
•	Lithium ion battery Lithium metal battery					
0	Lithium hybrid battery					
6. Pa	arameters					
Mass	in gram (g):	182				
Lithiu	m ion: Indicate watt-hour rating (Wh):	22.2				
Lithiu	Lithium metal: Indicate lithium metal content in gram (g):					
Lithiu	Lithium hybrid: Indicate lithium metal content in gram (g) and watt-hour rating (Wh):					
	William rigina. Indicate deficient in grain (g) and water loar rating (VVII).					
7 5						
/. Pi	nysical description of battery					
IC	CR 18650-2000mAh, 12V, 22.2 Wh					
8. Model numbers						
Α	AKKUPACK GAP 12-20					

#### **TESTS AND RESULTS**

9. List of tests conducted and results - Mark N/A, pass or fail with an "●"	N/A	pass	fail
T1 - Altitude simulation		•	0
T2 - Thermal Test		•	0
T3 - Vibration		•	
T4 - Shock		•	
T5 - External Short Circuit		•	
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm See check point 1a and 9a.	0	•	0
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells having a diameter of less than 18 mm. See check point 1a and 9a.	0	•	0
T7 - Overcharge		•	
T8 - Forced Discharge, only valid for cells. See check point 1a and 9a.			



IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

58493 AKKUPACK GAP 12-20

When the the mar	en no separate document for the cells inside the battery en no separate document for the cells is provided, this confirms that cells inside the battery (see checkpoint 1.a.) have successfully passed UN 38.3 test. In this case under checkpoint 9 the T.6 and T.8 must be ked as "passed" and here under 9.a. "Cell UN 38.3 Test confirmed" ds to be ticked.			38.3 T irmed	est	UN 38.3 confi	Cell Test NOT rmed	$\bigcirc$
10. F	Reference to assembled battery testing requirements							
							N/A	
11. F	Reference to the revised edition of the Manual of Tests and Criteria used and	d to	ame	ndme	nts the	ereto		
ADD	ITIONAL SUPPLIER INQUIRY							
[	Quality management system for manufacturing batteries  Does the manufacturer of the battery manufacture the products based on a documented quality management system according to transport regulations?				•	YES	NO	$\bigcirc$
l L	Are the following parameters exceeded? Lithium ion battery: more than 100 Wh Lithium metal battery: more than 2 g Lithium Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh				C	YES	NO	
Che	ck point 14 – 16 need to be answered when 13 has been ticked "YES":							
14. [	Does each battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?				$\Box$	YES	NO	
<b>15</b> . l	s each battery equipped with an effective means of preventing external short c	ircu	its?		O	YES	NO	<b>O</b>
6	s each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?		$\Big)$	N/A	C	YES	NO	
17 (	Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion batterie		nd li	ithium	nolua	nor hatto	rios	
	State of Charge (SoC) max. 30 %			N/A	Potgii	YES	NO	0
			_					

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

58493 AKKUPACK GAP 12-20

#### BATTERIES INSTALLED IN EQUIPMENT

18. Check point 18 needs to be answered when the batteries are installed in articles:					
18.a) Only button cells enclosed?	YES	NO O			
18.b) Number of enclosed batteries per equipment		3			
When the equipment is intentionally active/switched on during transport e.g. data loggers:					
18.c) Confirmation that no dangerous amount of heat is emitted from the equipment N/A	YES	NO O			
18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160	YES	NO			

19. Place, Date	20. Title, Surname, First name	21. Company stamp and signature	
Wolpertshausen, 03.12.2019	Matthias Moll	Digital unterschrieben von Matthias Moll Datum: 2019.12.04 14:32:15 +01'00'	